

STEELPUMPS

EVOLUTION

WP 15

Self priming, flexible impeller progressive cavity for hot water, diesel and heating oil. Single phase.

PLUS

- Pumping of warm clean water and olive oil
- Pumping liquids from boilers and aquariums
- Emptying of oil tank
- Bilge pump on boats
- Easily transportable
- No automatic pressure control

MATERIALS

- Pump body: Brass
- Motor body: Aluminium
- Rotor shaft: Stainless 304
- Impellers: NBR rubber
- Gaskets: NBR rubber
- Rear cap: Polypropylene
- Cables 1.5m with Schuko plug

ELECTRICAL FEATURES

Code	KW	HP	Current Amps	Cap. μ F
WP 15	0.12	0.16	1.6	8
Class F insulated motor				

HYDRAULIC FEATURES

Code	Q (l/m) FLOW						
	0	2.5	5	7.5	10	12.5	15
H HYDRAULIC HEAD (m)							
WP 15	12	10	8	6	4	2	0

PLEASE NOTE: the performances may be subject to change depending on the drained liquid

CHARACTERISTICS AND INSTALLATION

Drained Liquid	Hot water, heated fuel, oil
Max. Temperature	+65 °C

DIMENSIONS AND WEIGHTS

Code	Measurement (mm unless indicated)				Weight
	A	B	H	DNA	Kg
WP 15	225	56	170	3/4"	4.8

CE



PERFORMANCE CURVES

