

STEELPUMPS

E V O L U T I O N

X-MARE

Sea water pump, flexible impeller progressive cavity for sea water or clean water.

PLUS

Used on boat for pouring water, either sea water
Pumps liquid with impurities
Electric motor termically protected
Bilge pumps
Deck washing

MATERIALS

Pump body: Stainless 303 coated polymer
Rotor shaft: Stainless 303
Impellers: NBR rubber
Gaskets: NBR rubber
Rear cap: Polypropylene
Cables 1.5mm²

ELECTRICAL FEATURES

Code	KW	HP	Current Amps
X-MARE	0.29	0.4	1.5
Class F insulated motor		60 min on - 30 min off	

HYDRAULIC FEATURES

Code	Q (l/m) FLOW						
	0	5	10	15	20	25	30
H HYDRAULIC HEAD (m)							
X-MARE	10	9.2	8.6	8.1	7.1	5.5	1

CHARACTERISTICS AND INSTALLATION

Drained Liquid	Sea and Clean Water
Max. Kinematic viscosity	5.5 cSt

DIMENSIONS AND WEIGHTS

Code	Measurement (mm unless indicated)							Weight Kg
	A	N	H	H1	N1	DMN	DNA	
X-MARE	214	127	182	79	120	1/2"	1/2"	5.5



PERFORMANCE CURVES

