

# STEELPUMPS

E V O L U T I O N

## WP 15

Self priming, flexible impeller progressive cavity for hot water, diesel and heating oil. Single phase.

### PLUS

- Pumping of warm clean water and olive oil
- Pumping liquids from boilers and aquariums
- Emptying of oil tank
- Bilge pump on boats
- Easily transportable
- No automatic pressure control

### MATERIALS

- Pump body: Brass
- Motor body: Aluminium
- Rotor shaft: Stainless 304
- Impellers: NBR rubber
- Gaskets: NBR rubber
- Rear cap: Polypropylene
- Cables 1.5m with 3-Pin UK plug

### ELECTRICAL FEATURES

| Code                    | KW   | HP   | Current Amps | Cap. $\mu$ F |
|-------------------------|------|------|--------------|--------------|
| WP 15                   | 0.12 | 0.16 | 1.6          | 8            |
| Class F insulated motor |      |      |              |              |

### HYDRAULIC FEATURES

| Code                 | Q (l/m) FLOW |     |   |     |    |      |    |
|----------------------|--------------|-----|---|-----|----|------|----|
|                      | 0            | 2.5 | 5 | 7.5 | 10 | 12.5 | 15 |
| H HYDRAULIC HEAD (m) |              |     |   |     |    |      |    |
| WP 15                | 12           | 10  | 8 | 6   | 4  | 2    | 0  |

PLEASE NOTE: the performances may be subject to change depending on the drained liquid

### CHARACTERISTICS AND INSTALLATION

|                  |                             |
|------------------|-----------------------------|
| Drained Liquid   | Hot water, heated fuel, oil |
| Max. Temperature | +65 °C                      |

### DIMENSIONS AND WEIGHTS

| Code  | Measurement (mm unless indicated) |    |     |      | Weight |
|-------|-----------------------------------|----|-----|------|--------|
|       | A                                 | B  | H   | DNA  | Kg     |
| WP 15 | 225                               | 56 | 170 | 3/4" | 4.8    |

CE



### PERFORMANCE CURVES

